

DATASHEET

IS540.1



APPROVALS



ATEX approval: EX-Zone 1/21
 Ⓜ II 2G Ex ib IIC T4 Gb
 Ⓜ II 2D Ex ib IIIC T135°C Db



IECEx approval: EX-Zone 1/21
 Ex ib IIC T4 Gb
 Ex ib IIIC T135°C Db



NEC500 approval:
 Class I, II, III Division 1
 Groups A B C D E F G T4

Further approvals: PCEC (China) | TIIS (Japan) | INMETRO (Brazil) | IA (South Africa) | KCs (South Korea)

TECHNICAL FEATURES MODEL M540A01

Operating system	Android™ 14
Processor	Qualcomm® QCM6490 Octa Core
Memory	8 GB RAM 128 GB internal memory microSD memory up to 128 GB
Supported frequency bands	2G GSM: 850/900/1800/1900 MHz 3G WCDMA: B1/2/4/5/8 4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFB1 B13/14/17/20/25/26/28/29/30/66/71 4G LTE-TDD: B38/39/40/41/42/43/48 5G NR: n1/n2/n3/n5/n7/n8/n12/n20/n25/n28/n30/n38/n40/n41/n48/n66/n71/n77/n78/n79
Dimensions	Size: 180,0 x 84,9 x 20,6 mm weight: 422 g
Display	6" Corning® Gorilla® Glass 3 rd generation 1080 x 2160 pixels FHD
Battery	4400 mAh replaceable
Camera	48 MP AF rear camera 5 MP FF front camera
SIM support	1 nano SIM + eSIM
Connections	Wi-Fi® 6: IEEE 802.11 a/b/g/n/ac/ax/e/k/r/v Bluetooth® 5.2 GPS, A-GPS, Glonass, A-Glonass, Beidou, Galileo Near Field Communication (NFC)
Ports in/out	16-pin ISM interface USB-C
Sensors	Accelerometer, Gyroscope, Light, Magnetic, Proximity, Pressure sensors
Types of protection	IP68 dust-/waterproof MIL-STD-810H usable from -20 °C to +55 °C

FURTHER FEATURES

Red key top | Optional functions assignable via Button App (system integrated), e.g. LWP

Side key left | Optional functions assignable via Button App (system integrated)

Amplified loudspeaker

SET CONTENT

Smartphone, Battery, i.safe PROTECTOR 2.0 Type C USB Cable, Power Adapter universal, Screwdriver, Display Protection Foil, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.